



Safety Data Sheet

Issue Date: 03-May-2019

Revision Date: 06-May-2019

Version 1

1. IDENTIFICATION

Product identifier

Product Name Lithium EP Plus LP-10™ Grease

Other means of identification

SDS # MP-015

Recommended use of the chemical and restrictions on use

Recommended Use Semi-solid, multi-purpose, lithium grease.

Details of the supplier of the safety data sheet

Manufacturer Address

Muscle Products Corp
752 Kilgore Road
Jackson Center, PA 16133
www.musclelubricants.com

Emergency telephone number

Company Phone Number 1-814-786-0166
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Dark grey semi-solid

Physical state Semi-solid

Odor Petroleum

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

Signal Word

Warning

Hazard statements

Causes skin irritation
Causes serious eye irritation



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/eye protection/face protection

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of water and soap
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash it before reuse

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	30-60
Asphaltic Resin	8052-42-4	15-40
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	7-13

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Inhalation	Remove to fresh air.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms	Causes skin irritation. Causes serious eye irritation.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Storage temperature should not exceed 40°C (104°F) to maintain best product performance. 2-year shelf life.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphaltic Resin 8052-42-4	TWA: 0.5 mg/m ³ benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m ³ fume 15 min

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Semi-solid	Odor	Petroleum
Appearance	Dark grey semi-solid	Odor Threshold	Not determined
Color	Dark grey		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting point / freezing point	Not determined	
Boiling point / boiling range	149 °C / 300.2 °F	(ASTM D-92)
Flash point	255 °C / 437 °F	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Flammability Limit in Air		
Upper flammability or explosive limits	Not determined	
Lower flammability or explosive limits	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	0.94232	g/cm3 @ 20°C (68°F)
Water Solubility	Not miscible	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Product is not self igniting	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Petroleum products tend to soften or swell most natural rubbers.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact	Causes skin irritation.
Inhalation	Do not inhale.
Ingestion	Do not ingest.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	> 15000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 2400 mg/m ³ (Rat) 4 h
Asphaltic Resin 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity This product is not known to contain carcinogenic substances. This product contains mineral oils which are considered to be severely refined and not carcinogenic under IARC. All of the oils in this product contain less than 3% extractables by IP 346.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	A2	Group 1	Known	X
Asphaltic Resin 8052-42-4		Group 2B		X
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	A2	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0		5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5		5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Asphaltic Resin 8052-42-4	>6

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Petroleum distillates, solvent dewaxed heavy paraffinic	X	X	X		X	X	X	X
Asphaltic Resin	X	X	X	X	X	X	X	X
Petroleum distillates, hydrotreated heavy naphthenic	X	X	X		X	X	X	X
Proprietary organic compound	X						X	

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances**AICS - Australian Inventory of Chemical Substances***US Federal Regulations****CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Asphaltic Resin 8052-42-4	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	2	1	0	Not determined

Issue Date: 03-May-2019
 Revision Date: 06-May-2019
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet