



Penetrating Oil SL-10™

Heavy-duty penetrating oil and spray lubricant designed to quickly penetrate into hard-to-reach areas to loosen seized and corroded nuts and bolts and provide long-lasting lubrication

Key Features & Benefits

- Dual function: Fast-acting penetrating oil and heavy-duty lubricating action
- Penetrates into hard-to-reach areas
- Loosens seized and corroded nuts and bolts or other frozen metal mechanisms
- Protects against rust and corrosion
- The better alternative to an aerosol can... the spray bottle is safer and full of product... no money wasted on hazardous ozone-depleting substances
- Contains **Muscle Metal Treatment MT-10®** technology **Power-Lift Grease PL-10™** for superior lubrication

- Any other industrial, automotive, or commercial area of lubrication that requires an external, heavy-duty penetrating oil or spray lubricant.
- Need extra rust protection in corrosive conditions? Try **Muscle Extreme Conditions SL-10™**.

Directions for Use

Wipe off exposed metal surfaces. Spray **SL-10™** directly onto areas to be lubricated. After application, wipe away excess lube with a dry cloth. Repeat in especially stubborn applications.

Typical Applications

- Rusty nuts & bolts
- Heavy-duty industrial chains
- Braided steel cables
- Wire rope
- Chain drives
- Drag lines
- Linkages
- Open roller bearings
- Sleeve bearings
- Couplings
- Bushings
- Pulleys
- Hinges
- Augers
- Tools
- Metal mechanisms
- Assembly lube during transmission rebuilds
- Protection during long-term storage

Technical Data

Appearance.....	Milky amber liquid
Odor.....	Mild petroleum
Boiling point	399°F (204°C) D1120
Flash point	295°F (146°C) D93
Specific gravity @ 60°F, g/cm ³	0.933 D1298
Lbs per gal (U.S.).....	~ 7.785
Viscosity @ 40°C	23 - 26 cSt
Pour point.....	- 33°F (-36°C) D97
Rust test, 4 hr.....	Pass (no rust) D665A
Solubility.....	Insoluble (water)

The above properties are typical values and do not constitute a product specification.

Container Availability

Item SL-10-16WS.....	16 oz. w/sprayer (473 mL)
Item SL-10-16	16 oz. bottle only (473 mL)
Item SL-10-128	1 U.S. gallon (3.7 L)
Item SL-10-5G.....	37 lbs net wt / pail
Item SL-10-55G.....	425 lbs net wt / drum



MUSCLE PRODUCTS CORP.

Additives and Lubricants Engineered for Performance

752 Kilgore Road | Jackson Center, PA 16133 USA | 814-786-0166 | musclelubricants.com

Registered:
ISO 9001